

INVERTER GENERATOR  
Output: 2kW-4kW



HYUNDAI  
POWER EQUIPMENT

INVERTER GENERATOR

- Air Cooled Engine
- IP 23 Protection
- Gasoline Engine
- Noise Compliant

Feature:

- 22% Fuel consumption Ratio lower, Long run time;
- 57dBA lower noise;
- THD <2% available directly to power precision equipment;
- Only 22kg, compact design.



SPECIFICATION

| Item      |                                | Technical Specifications                      |                     |
|-----------|--------------------------------|-----------------------------------------------|---------------------|
| Generator | Model                          | HY4000Si                                      | HY4000i             |
|           | Type                           | Inverter                                      | Open Frame Inverter |
|           | Max. AC Output(Kw)             | 4                                             | 4                   |
|           | Rate. AC Output(Kw)            | 3.6                                           | 3.6                 |
|           | Noise(dB/7m)                   | 70                                            | 75                  |
|           | Fuel Tank Capacity(L)          | 10                                            | 11                  |
|           | Running Time At 50% Loading(H) | 12                                            | 14                  |
|           | Dimension(L×W× H mm)           | 500×400×460                                   | 500×400×460         |
|           | Net Weight(Kg)                 | 37                                            | 35                  |
|           | Optional                       | Parallel, DC, USB, Lighter Output             |                     |
| Engine    | Engine Model                   | LT225Vi                                       | LT225Vi             |
|           | Engine Type                    | Single Cylinder, Forced Air-Cooling, 4-stroke |                     |
|           | Starting System                | Recoil/Electric                               | Recoil/Electric     |
|           | Bore×Stroke(mm)                | 70x59                                         | 70x59               |
|           | Displacement(cc)               | 223                                           | 223                 |
|           | Fuel Consumption(g/kw.h)       | ≤450                                          | ≤450                |